

TerraTrack Lite

TerraTrack Lite Nonwoven Geotextile



CHARACTERISTIC	VALUE
Description	TerraTrack Lite Nonwoven Geotextile

SPECIFICATION

GENERAL INFORMATION

Stock code	GTERRALITE
Range	TerraTrack
Third party certified	CE
Roll sizes	1m x 14m 2.25m x 25m 2.25m x 50m

GEOTEXTILE PROPERTIES

Material		Polypropylene
Tensile strength (MD)	EN ISO 10319	6.5kN/m
Tensile strength (CMD)	EN ISO 10319	6.9kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	65%
Dynamic perforation resistance	EN ISO 13433	38mm
CBR puncture resistance	EN ISO 12236	1100N
Predicted minimum durability		100 years
Maximum allowed time	EN 12224	4 weeks
Water permeability	EN ISO 11058	120L/m ² .s
Characteristic opening size	EN ISO 12956	110µm
Permeability	EN ISO 11058	120L/m ² .s

- Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
- It is the responsibility of all users to satisfy themselves the above data is current.
- Installation details are available in the [knowledge base](#).
- All Geoworks products are supplied subject to our [terms and conditions of sale](#).
- Some imagery within our materials is illustrative in nature and may not depict the exact product supplied.

