

TerraTrack Pro

Superior Nonwoven Geotextile, 4000N, 300g/m² - 4.5m x 90m roll



CHARACTERISTIC	VALUE
Description	Superior Nonwoven Geotextile, 4000N, 300g/m ² - 4.5m x 90m roll

SPECIFICATION

GENERAL INFORMATION

Stock code	GTERRAPRO/45X90
Range	TerraTrack
Third party certified	CE
Roll sizes	4.5m x 90m
Geotextile product range	TerraTrack

GEOTEXTILE PROPERTIES

Tensile strength (MD)	EN ISO 10319	22kN/m
Tensile strength (CMD)	EN ISO 10319	22kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	55%
Dynamic perforation resistance	EN ISO 13433	12mm
CBR puncture resistance	EN ISO 12236	4000N
Dynamic cone drop	EN ISO 13433	12mm
Water permeability	EN ISO 11058	60L/m ² .s
Characteristic opening size	EN ISO 12956	90µm
Thickness under 2kPa	EN ISO 9863-1	2.4mm
Weight	EN ISO 9864	300g/m ²

NOTES

Oil retention (l/10m²): >6

- ▶ Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
- ▶ It is the responsibility of all users to satisfy themselves the above data is current.
- ▶ Installation details are available in the [knowledge base](#).
- ▶ All Geoworks products are supplied subject to our [terms and conditions of sale](#).
- ▶ Some imagery within our materials is illustrative in nature and may not depict the exact product supplied.